To: All Plan Holders of Record

From: City of Mentor
8500 Civic Center Boulevard
Mentor, OH 44060

Re: ***Addendum No. 1***
2015 Road Repair Program
City of Mentor

Date: February 5, 2015

This Addendum forms a part of the contract documents and modifies the original bidding documents dated January 2015. Acknowledge receipt of this addendum in the space provided on the "proposal forms." Failure to do so may subject the bidder to disqualification.

BID OPENING DATE

The bid opening date shall be changed from Friday, February 6, 2015 to Friday, February 13, 2015. The time and place of opening shall remain the same.

BID DOCUMENTS

1. Replace Prices to Include, Page BD.10 with the enclosed Prices to Include, Page BD.10A.

AEP:aep

O:\APPS\PROJECTS\R39602_Road Repair Program\2015 Road Program\Bid Documents\Addendum 1.docx

3.1 FULL DEPTH PAVEMENT REMOVAL AND RIGID REPLACEMENT, CLASS QC MS, AS PER PLAN

Basis of Payment

Payment shall be made in accordance with ODOT Item 255 and shall also include all General Items 1.1 to 1.11 above and the cost for all full depth diamond blade saw cutting regardless of existing pavement thickness, removal of existing pavement regardless of existing pavement thickness, proof rolling, subgrade compaction and preparation, integral curb, 3" sub-base course of ODOT Item 304 (if subbase course does not already exist), reinforcing steel, steel dowels, joint sealers, temporary drives or provisions for access, and seeding and mulching of all disturbed areas. **(5/8" hook bolts on 18" centers may be used in lieu of steel dowels for transverse joints)** Width of Pavement Joint repair shall be as directed by the engineer. Note: Engineer will mark pavement replacement area before saw cutting and will include repair area quantity. If the contractor disagrees with quantity as marked, contractor shall contact the engineer prior to cutting the pavement. Otherwise the quantity indicated by the engineer shall be considered final measured quantity.

3.2 FULL DEPTH PAVEMENT REMOVAL AND RIGID REPLACEMENT, (FULL SLAB), CLASS QC MS, AS PER PLAN

Basis of Payment

Payment shall be made in accordance with ODOT Item 255 and shall also include all General Items 1.1 to 1.11 above and the cost for all full depth diamond blade saw cutting regardless of existing pavement thickness, removal of existing pavement regardless of existing pavement thickness, proof rolling, subgrade compaction and preparation, integral curb, 3" sub-base course of ODOT Item 304 (if subbase course does not already exist), reinforcing steel, steel dowels, joint sealers, temporary drives or provisions for access, and seeding and mulching of all disturbed areas. **(5/8" hook bolts on 18" centers may be used in lieu of steel dowels for transverse joints)** Width of Pavement Joint repair shall be as directed by the engineer but shall be no less than a full slab in length and width. Note: Engineer will mark pavement replacement area before saw cutting and will include repair area quantity. If the contractor disagrees with quantity as marked, contractor shall contact the engineer prior to cutting the pavement. Otherwise the quantity indicated by the engineer shall be considered final measured quantity.